

**BEST
PRACTICE**



EBA 20
Small Centrifuge

Practical and handy, the EBA 20 is ideal for a small quantity of samples. The small, microprocessor-controlled centrifuge is supplied with an 8-place angle rotor. It accepts a variety of tubes up to a volume of 15 ml and generates a max. speed of 6,000 min⁻¹, corresponding to 3,421 RCF.

Angle rotor 8-place

↙33°



TECHNOLOGY EBA 20

Small centrifuge, with rotor		
Power supply ^{*)}	208–240 V 1 ~	100–127 V 1 ~
Frequency	50–60 Hz	
Consumption	65 VA	70 VA
Emission	EN 55011 group 1, class B EN 61000-3-2 EN 61000-3-3	FCC class B
Immunity	EN 61000-6-1	-

Max. capacity	8 x 15 ml
Max. RPM (speed)	6,000 min ⁻¹
Max. RCF	3,461
Running time	1–99 min, ∞ continuous run, short cycle mode (impulse key)

Dimensions (H x W x D)	216 x 231 x 292 mm
Weight	approx. 4 kg

Cat. No.	2002	2002-01
----------	------	---------

capacity in ml	4	5	15	1.1–1.4	2.6–2.9	2.7–3	4.5–5	4.9	7.5–8.2	9–10	10	1.6–5	4–7	8	8.5–10	15	
Ø x L in mm	10x88	12x75	17x100	8x66	13x65	11x66	11x92	13x90	15x92	16x92	15x102	13x75	13x100	16x125	16x100	17x120	
Cat. No.	-	0553 ¹⁾	0518 ¹⁾	blood collection/urine tubes												0509	
rotor incl.																	
Cat. No.	6305	1054-A	-	1054-A				-				1054-A		-			
boring Ø x L in mm	11.5x67.5	13.5x60	17.7x88	13.5x60				17.7x88				13.5x60		17.7x88			
tubes per rotor	8								8	8	4	8	4				
max. RCF	2,817	2,697	3,461	2,697				3,461				2,697	3,461				
radius in mm	70	67	86	67				86				67	86				
run-up in sec	26																
run-down in sec	☐ 37 ☉ 121																

*) Other voltages on request.

1) Please make sure not to exceed the tubes' max. permissible RCF. The max. RCF for glass tubes is 4,000.

Andreas Hettich GmbH & Co. KG

Föhrenstr. 12
D-78532 Tuttlingen
Germany
www.hettichlab.com
info@hettichlab.com
service@hettichlab.com

Phone +49 (0)7461 / 705 -0
Fax +49 (0)7461 / 705 -122

National Sales: -200
International Sales: -201
National Service: -202
International Service: -112